



Original equipment manufacturer uses Siemens pressure transmitters to add value and reliability to their steam generators

Situation

A large OEM (Original Equipment Manufacturer) of Process and Heating Boilers/Steam Generators provides boilers/steam generators to industrial plants for processing applications. The type of steam generator they supply is often a forced-recirculation water-tube boiler that uses a drum as a steam separator with a reservoir of water to supply the coils. A re-circulating pump draws the water from the drum and forces it through a set of parallel connected coils at the rate of 3 to 4 times the maximum steaming rate.

The water is then pushed through a steam lance and a series of baffles in the drum where some of the water is flashed into steam and separated. The dry steam is released and the water is re-circulated through the coils. The fuel and combustion air is controlled by a modulating motor that responds to steam pressure. The feedwater is controlled by a water level control system and modulating feedwater valve. As part of the package, the company supplies transmitters on the steam generators to measure the water levels in the expansion tanks used to put water in the boiler and recover steam after the heat exchanger. This is a critical

measurement because without constant and consistent water supply, the boilers can become inefficient and could meltdown or explode.

Challenge

This company was previously using a float type of level measurement device on their steam generators with 0-135 ohm output. It was difficult to find control valves that could match the 0-135 ohm output. It was also difficult to adjust the transmitter's span. Because the transmitters did not have local displays, the technicians could not see the current reading onsite. In addition, the company stocked replacement transmitters for their customers, but were at risk of having the transmitter warranties expire while still on the shelf.

Solution

The local Siemens representative demonstrated the capabilities of the SITRANS P DS III differential pressure transmitter for this level measurement application on boiler/steam generators. The company now supplies the Siemens differential pressure transmitters to measure the water levels in the expansion tanks. The DS III DP transmitters come standard with a built in local display, pushbutton calibration and span adjustments on the unit, and a 5-year "powered" warranty. The warranty period does not start until the unit is installed and powered up.

Process Instrumentation & Analytics

www.usa.siemens.com/pi

SIEMENS

The Siemens transmitters feature an accuracy of $\leq 0.075\%$, extensive diagnostic and simulations functions, and a choice of communication protocols, including HART, PROFIBUS PA, PROFIsafe, or FF. The SITRANS P DS III DP transmitter is suitable for installation in SIL 2 applications in accordance with IEC 61508/IEC 61511.

Benefits

- **Cost savings:** 5-year “powered” warranty saves on replacing stocked instruments because the warranty period does not start until the instrument is actually put into service.
- **Ease of use:** The ability to use the pushbutton keypad on the instrument to configure and calibrate makes start up quick and easy. The built-in display allows the user to see the current readings without having to go back to the control room. Choice of communication protocols makes it easy to use with almost any system.
- **Time savings:** Extensive diagnostic and simulation functions make it easy to pinpoint any faults that might arise.



Siemens Industry, Inc.
Industry Automation
3333 Old Milton Parkway
Alpharetta, GA 30005

1-800-241-4453
info.us@siemens.com

www.usa.siemens.com/pi

Subject to change without prior notice
Order No.: PICS-00056-1010
All rights reserved
Printed in USA
©2010 Siemens Industry, Inc.

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual use do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.

All product designations may be trademarks or product names of Siemens AG or supplier companies whose use by third parties for their own purposes could violate the rights of the owners.